

## HIGH PERFORMANCE BRAIDED REDUCING CONNECTORS

### REDUCER—FLANGE X FLANGE

- **Stainless Steel**  
Annular Hose with Stainless Steel Braid
- **150# Drilling Carbon Steel**  
Plate Flange

Large Hose ID	Small Hose ID	OAL	Approx. Wt. (lbs.)	Max Working Pressure @ 70°F
2"	1-1/2"	13"	12	435
2-1/2"	1-1/2"	13"	15	350
2-1/2"	2"	13"	15	350
3"	2"	13"	18	325
3"	2-1/2"	13"	19	325
4"	2"	13"	22	270
4"	2-1/2"	13"	25	270
4"	3"	13"	25	270
5"	2-1/2"	16"	30	200
5"	3"	16"	30	200
5"	4"	16"	34	200
6"	3"	17"	38	185
6"	4"	17"	40	185
6"	5"	17"	42	185
8"	4"	18"	55	235
8"	5"	18"	58	235
8"	6"	18"	60	235
10"	6"	20"	85	260
10"	8"	20"	95	260
12"	10"	22"	125	160

### REDUCER—FLANGE X GROOVE END

- **Stainless Steel**  
Annular Hose with Stainless Steel Braid
- **150# Drilling Carbon Steel Plate**  
Flange X Sch 40 Precision Grooved End

Large Hose ID	Small Hose ID	OAL	Approx. Wt. (lbs.)	Max Working Pressure @ 70°F
2"	1-1/2"	14"	12	435
2-1/2"	1-1/2"	14"	15	350
2-1/2"	2"	14"	15	350
3"	2"	14"	18	325
3"	2-1/2"	14"	19	325
4"	2"	16"	22	270
4"	2-1/2"	16"	25	270
4"	3"	16"	25	270
5"	2-1/2"	18"	30	200
5"	3"	18"	30	200
5"	4"	18"	34	200
6"	3"	19"	38	185
6"	4"	19"	40	185
6"	5"	19"	42	185
8"	4"	20"	55	235
8"	5"	20"	58	235
8"	6"	20"	60	235
10"	6"	22"	85	260
10"	8"	23"	95	260
12"	10"	23"	125	160

QUICK DELIVERY

CUSTOM SIZES AVAILABLE

Toll Free: 877-462-1007  
Fax: 847-462-1450  
24/7 Emergency Service: 847-337-9459

[www.duraflexinc.com](http://www.duraflexinc.com)



© Copyrights 2004-2009 Duraflex, Inc.™ All rights reserved.

765 Industrial Drive  
Cary, IL 60013

Em: [duraflex@duraflexinc.com](mailto:duraflex@duraflexinc.com)

## HIGH PERFORMANCE BRAIDED FLEXIBLE CONNECTORS

### MALE PIPE THREADS



- Stainless Steel Annular Hose with Stainless Steel Braid
- Carbon Steel Male Pipe Threads

I.D.	OAL	Approx. Wt. (lbs.)	Max Working Pressure @ 70°F
1/2"	6-1/2"	1/2	825
3/4"	7"	3/4	600
1"	8"	1	580
1-1/4"	8-1/2"	1-1/4	535
1-1/2"	9"	1-1/2	510
2"	10-1/2"	2-1/2	442

### FLANGE



- Stainless Steel Annular Hose with Stainless Steel Braid
- 150# Drilling Carbon Steel Black Enamel Baked Plate Flange

I.D.	OAL	Approx Wt. (lbs.)	Max Working Pressure @ 70°F
2"	9"	11	442
2-1/2"	9"	14	390
3"	9"	15	325
4"	9"	20	270
5"	11"	28	185
6"	11"	33	170
8"	12"	52	185
10"	13"	75	180

5 YEAR WARRANTY

STOCK PUMP CONNECTORS

