



DURA-LOCK[™]



- **STRIP WOUND HOSE**
- **UNPACKED / PACKED TYPES**



INTERLOCKED FLEXIBLE TUBING

- ELECTRICAL CONDUIT
- UV & EM SHIELDING
- ARMOR CASING
- FLEXIBLE EXHAUST TUBING
- TAR & ASPHALT TRANSFER
- HIGH VELOCITY FLOW LINERS for CORRUGATED HOSE ASSEMBLIES
- FLEXIBLE METAL HOSE OUTER GUARDS
- BEVERAGE DISPENSING TUBE GUARD
- COSMETIC COVERINGS for ELECTRICAL APPLIANCE WIRING
- MOTORCYCLE CABLE PROTECTORS
- CONVEYANCE HOSE for DUST, LINT and MISC. DEBRIS
- FUME HOOD & WELD BOOTH DUCTING

BENEFITS / ADVANTAGES

- SUPPLIER to DISTRIBUTORS and LARGE END USERS
- MOST ITEMS ALWAYS IN STOCK
- FLOPPY or RIGID CONFIGURATIONS AVAILABLE
- LARGEST SELECTION of BASE MATERIAL & PACKING MATERIAL
- LARGEST SELECTION of INSIDE and OUTSIDE DIAMETER COMBINATIONS
- ENGINEERING, DESIGN and APPLICATION ASSISTANCE IN - HOUSE



DURA-LOCK™



STANDARD SIZES

| Nominal I.D. | Nominal O.D. | Inside Bending Diameter | Approx. Weight "C" Feet | Nominal I.D. | Nominal O.D. | Inside Bending Diameter | Approx. Weight "C" Feet |
|--------------|--------------|-------------------------|-------------------------|--------------|--------------|-------------------------|-------------------------|
| 1/4" | .375" | 3" | 11 | 2-1/8" | 2.280" | 15-1/2" | 72 |
| 3/8" | .500" | 4" | 14 | 2-1/4" | 2.410" | 16-1/2" | 76 |
| 1/2" | .625" | 6" | 16 | 2-3/8" | 2.530" | 17-1/2" | 81 |
| 5/8" | .750" | 6-1/2" | 18 | 2-1/2" | 2.660" | 18-1/2" | 85 |
| 3/4" | .875" | 6-1/2" | 20 | 2-3/4" | 2.910" | 20" | 93 |
| 7/8" | 1.000" | 7" | 24 | 2-7/8" | 3.030" | 21" | 97 |
| 1" | 1.130" | 7-1/2" | 28 | 3" | 3.160" | 22" | 102 |
| 1-1/8" | 1.260" | 8-1/2" | 32 | 3-1/4" | 3.410" | 24" | 110 |
| 1-1/4" | 1.380" | 9-1/2" | 36 | 3-1/2" | 3.660" | 26" | 118 |
| 1-3/8" | 1.510" | 10" | 38 | 3-3/4" | 3.910" | 27" | 127 |
| 1-1/2" | 1.650" | 11" | 48 | 4" | 4.160" | 29" | 135 |
| 1-5/8" | 1.780" | 12" | 52 | 4-1/2" | 4.660" | 33" | 152 |
| 1-3/4" | 1.900"® | 13" | 58 | 5" | 5.170" | 37" | 168 |
| 1-7/8" | 2.030" | 14" | 60 | 6" | 6.170" | 44" | 200 |
| 2" | 2.160" | 15" | 66 | | | | |

OPTIONS

- **MATERIALS AVAILABLE** Aluminum Galvanized or Stainless Steel
- **FLEXIBILITY** Standard or Floppy
- **CONFIGURATION TYPES** Interlock or Squarelock
- **PACKING TYPES** Unpacked or Packed
SS, Norfab or Copper Wire
- **ASSEMBLY FITTING TYPE** NPT, Plate Flange, Slip-On Flange, Cam-Lock, Weld End, Farm Flange, Groove Type, Tube End, Female Swivel, Quick Release, Reducer or Sweat
- **BORE TYPE** Smooth or Corrugated
- **OTHER OPTIONS** Plastic Gas Tight Covering, Metal or Paper Tagging, Material Certs

