

Flexible Solutions

DURAFLEX™ INC.

for Rigid Applications

DETAILS

PRODUCT

DURA-SHIELD THERMAL INSULATION COVERS™

STANDARD DURA-SHIELD THERMAL COVERS™

Exhaust Connector Sizes	Thickness	Length
3.500"	1"	18"
4.500"	1"	18"
5.563"	1"	18"
6.625"	1"	18"
8.625"	1"	18"




DURA-SHIELD THERMAL INSULATION COVERS™

Designed for high quality, extreme temperatures and enduring exhaust systems.

- Alumina-Silica Ceramic Fiber cover is highly pure.
- Silicone Resins infused into netted Fiberglass.
- Kevlar threads are durably sutured to the reusable cover.
- **DURA-SHIELD THERMAL INSULATION COVERS™** are damage resistant.
- The **DURA-SHIELD THERMAL INSULATION COVERS™** is designed for up to 1000° F operating temperatures.
- Covers that are dampened with water, steam or oil revert back to original material & thermal make-up once dried.
- **DURA-SHIELD THERMAL INSULATION COVERS™** buffer reverberation.
- Compliant with U.S.C.G. #164.009 noncombustible requirements.
- 18" wide rolls available with double-stitch every 6" to simplify installation.

Custom orders are welcomed!

DURAFLEX, INC.™ | 765 INDUSTRIAL DRIVE, CARY, IL 60013
PHONE 877.462.1007 | FAX 847.462.1450 | E-MAIL info@duraflexinc.com
www.duraflexinc.com | 24/7 EMERGENCY | 847.337.9459



© Copyrights 2012 Duralflex, Inc.™ All rights reserved.

